

**POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES  
FLAME RETARDANT LEAD FREE (FRLF) / FLAME RETARDANT LOW SMOKE (FRLSH) / HEAT  
RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE CONFORMING TO IS-694:2010  
WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100  
VOLTS**

**POLYCAB PVC INSULATED SINGLE CORE  
UNSHEATHED INDUSTRIAL(MULTISTRAND)  
CABLES – HALOGEN FREE FLAME RETARDANT  
(HFFR) WITH BRIGHT ANNEALED ELECTROLYTIC  
BARE COPPER CONDUCTOR FOR VOLTAGE  
GRADE 1100 VOLTS**

Size (sq.mm.)	FRLF	FRLS-H	GREEN WIRES HR-FRLS-H-LF	HFFR	Coils Per Box
	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	
0.75	5980	6165	6280	6495	10
1	7845	8075	8205	8415	8
1.5	11540	11885	12050	12400	6
2.5	18715	19290	19570	20140	4
4	19250	19830	20115	20705	4
6	28780	29650	30095	30955	3
10	50425	51905	52665	54165	1
16	79945	82300	83500	85885	1

**Notes**

1. The above rates are exclusive of GST which shall be charged extra.
2. This Price List is subject to change without notice.
3. As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.