



PRICE LIST (FLEXIBLE CABLES) wef. 12.12.2025

"RALLISON" Multistranded Copper Conductor Industrial cable , HRFR/FRLS PVC/ZHFR Insulated 1100 volts confirming to IS 694/2010 / 17048

S. No.	Cond. Area	Cond. Const.	Current Rating	Master Carton (Coils)	Rs. per 180 mtrs. Coil				
					FR PVC	HRFR PVC	FRLS PVC	ZHFR	FS
	(Sqmm)	(No/dia in mm)	(Amp)	180Mtrs					
1	0.75	24/0.2	8	12	4165	4300	4300	4510	6355
2	1	32/0.2	13	12	5490	5685	5685	5955	8390
3	1.5	30/0.25	18	10	8350	8590	8590	9000	12630
4	2.5	50/0.25	24	5	13565	13930	13930	14585	20445
5	4	56/0.3	32	4	20270	20750	20750	21745	30400
6	6	84/0.3	41	3	30970	31640	31640	33140	46300

"RALLISON" Flexible Industrial Cables, Copper Conductor, HRFR/FRLS PVC/ZHFR Insulated 1100 volts confirming to IS 694/2010 / 17048

S. No.	Cond. Area	Cond. Const.	Current Rating	Rs. per 100	Rs. per 100 mtrs.	Rs. per 100	Rs. per 100mtrs	Cond. Area
				mtrs. Coil	mtrs. Coil			
	(Sqmm)	(No/dia in mm)	(Amp)	FR PVC	HRFR PVC	FRLS PVC	ZHFR	(Sqmm)
7	0.5	16/0.2	5	1665	1710	1710	1790	0.5
8	0.75	24/0.2	8	2325	2400	2400	2505	0.75
9	1	32/0.2	13	3055	3160	3160	3305	1
10	1.5	30/0.25	17	4650	4775	4775	5000	1.5
11	2.5	50/0.25	24	7550	7740	7740	8105	2.5
12	4	56/0.3	30	11270	11530	11530	12085	4
13	6	84/0.3	38	17210	17580	17580	18420	6
14	10	80/0.4	52	30785	31240	31240	32910	10
15	16	126/0.4	70	48650	49365	49365	51980	16
16	25	196/0.4	88	75480	76575	76575	80585	25
17	35	276/0.4	110	105850	107390	107390	112935	35
18	50	396/0.4	145	153125	155885	155885	163345	50
19	70	354/0.5	215	216795	219915	219915	231100	70
20	95	484/0.5	260	285985	290900	290900	304845	95
21	120	608/0.5	305	365365	370630	370630	389320	120
22	150	750/0.5	355	456875	464595	464595	486845	150
23	185	925/0.5	415	553340	561305	561305	589655	185
24	240	1210/0.5	500	732505	743075	743075	780650	240
25	300	1527/0.5	585	913280	928480	928480	972950	300
26	400	2036/0.5	695	1220655	1240740	1240740	1300185	400

"RALLISON" Telephone Cables confirming to ITD specification S/WS-113C & 114D and colour code as per ITD S/WS-129D

S. No.	No of Pairs	Rate Rs. per 90 mtrs. Coil		
		Cond. Dia 0.40 mm	Cond. dia 0.50 mm	Cond. dia 0.60 mm
27	1 (Flat)	1185	1750	2210
28	2	1910	2975	3740
29	3	2760	4290	5370
30	4	3550	5620	7080
31	5	4570	6705	8415
32	10	9125	13840	17365
33	20	18255	28020	34800
34	50	45410	66730	
35	100	90560	133575	

- As per International practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is normal. The size of the conductor is determined by resistance. The construction of the conductor is as per market convention.
- This cancels all our previous Price - Lists
- Rates are exclusive of Sales Tax, Octroi etc and are subject to change without notice
- All disputes are subject to Delhi jurisdiction only.