

**POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES
FLAME RETARDANT LEAD FREE (FRLF) / FLAME RETARDANT LOW SMOKE (FRLSH) / HEAT
RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE CONFORMING TO IS-
694:2010 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE
GRADE 1100 VOLTS**

**POLYCAB PVC INSULATED SINGLE CORE
UNSHEATHED INDUSTRIAL(MULTISTRAND)
CABLES – HALOGEN FREE FLAME RETARDANT
(HFFR) WITH BRIGHT ANNEALED
ELECTROLYTIC BARE COPPER CONDUCTOR FOR
VOLTAGE GRADE 1100 VOLTS**

Size (sq.mm.)	FRLF	FRLS-H	GREEN WIRES HR-FRLS-H-LF	HFFR	Coils Per Box
	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	
0.75	5530	5700	5795	6000	10
1	7255	7470	7590	7780	8
1.5	10670	10995	11145	11475	6
2.5	17320	17850	18105	18630	4
4	17810	18350	18610	19155	4
6	26630	27435	27845	28645	3
10	46675	48035	48745	50125	1
16	73250	75405	76510	78690	1

Notes

1. The above rates are exclusive of GST which shall be charged extra.
2. This Price List is subject to change without notice.
3. As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.