



# Indersons

An ISO 90001:2000 Company

*Electrifying Places*

S-11 Janta Market Rajouri Garden, New Delhi-27

Ph: 011 4724 3000

email: sales@indersonsindia.com

Web: www.indersonsindia.com

Online portal: www.bestofelectricals.com

## Copper and GI Earthing Items

### Weight/Length Unit Conversion Table (Approx.)

No.	Item Type	Size	Copper Weight (kg)	Equip Length (mtr)	GI Weight (kg)
1	Strip/Patti	20x3	X	1	0.5
2	Strip/Patti	25x3	0.7	1	0.65
3	Strip/Patti	25x4	0.9	1	X
4	Strip/Patti	25x5	1.1	1	1.2
5	Strip/Patti	25x6	1.25	1	1.25
6	Strip/Patti	32x3	0.85	1	x
7	Strip/Patti	32x6	1.6	1	1.6
8	Strip/Patti	38x6/40x6	2.1	1	1.9
9	Strip/Patti	50x3	1.35	1	
10	Strip/Patti	50x5	2.25	1	2.5
11	Strip/Patti	50x6	2.7	1	2.4
12	Strip/Patti	50x8	x	1	3.4
13	Strip/Patti	50x10	-	1	4.5
14	Strip/Patti	75x6	4	1	
15	Strip/Patti	75x8		1	4.8
16	Strip/Patti	125x10	11.1	1	
16	Plate/Sheet	1' x 1' x 0.5mm	1	Each	x
17	Plate/Sheet	1' x 1' x 2mm		Each	2
18	Plate/Sheet	1' x 1' x 3mm	2.5	Each	x
19	Plate/Sheet	1' x 1' x 6mm	5	Each	x
20	Plate/Sheet	2' x 2' x 3mm	10	Each	7
21	Plate/Sheet	2' x 2' x 6mm	18	Each	15
22	Wire	6 No.	x	5.5	1
23	Wire	8 No. (4mm)	1	8	1
24	Wire	10 No.	1	13	1
25	Wire	12 No.	1	20	x
26	Wire	14 No.	x	22	1
27	Wire	13.25 No.	1	26	x

All figures are estimated and Indersons is not responsible for any mistakes

#### Other Earthing Items Available at Indersons besides above

GI Nut Bolt with double washer 25mm x 8mm

GI Nut Bolt with double washer 65mm

GI Earthing Electrode (GI Pipe 3m/15ft length). Typical Dia 40mm. Quality Light, Medium & Heavy

Salt/Coal - as per kg

CI main hole cover

CI Funnel with GI wire Mesh 1.5" (used with 50mm pipe)

CI Funnel with GI wire Mesh 0.75" (used with smaller size pipes)

Copper Chemical Earthing 2M - 2m Copper Rod filled with Chemical + 1 Bag

Copper Chemical Earthing 3M - 3m Copper Rod 80mmx3mm filled with Chemical + 2 Bags

GI Chemical Earthing 3M - 3m GI Rod 80mm x3mm filled with Chemical + 2 Bags (pipe Weight 15kg)

GI Chemical Earthing 2M - 2m GI Rod filled with Chemical + 1 Bag

Extra Bag available (Bag weight 25kg)

LT Panel Mats 2m x1m x thickness 6mm, 10mm & 12mm

Heat Shrink Sleeve 2.5mm min 100m