

PRICE LIST : 19th APR 2024

LP NO. KEI/HW/LP/24-25/02 DT.19.04.2024

INDUSTRIAL MULTI STRAND CABLES

HSN CODE : 85.44.60.20

KEI HOMECAB - FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

| CONDUCTOR (AREA SQ.MM) | NO. & SIZE OF WIRE IN MM | Casing (In Conduit / Trunking) | Unenclosed Clipped Directly to surface or on cable tray | STANDARD PACKING FOR 90 MTR. | RATE PER 90MTR. COIL |
|---------------------------|--------------------------------|--------------------------------------|---|------------------------------------|-------------------------|
| 0.50 | 16/0.20 | 4 | 4 | 28 | 1120 |
| 0.75 | 24/0.20 | 7 | 8 | 28 | 1500 |
| 1.00 | 32/0.20 | 12 | 13 | 24 | 1930 |
| 1.50 | 30/0.25 | 14 | 17 | 16 | 2880 |
| 2.50 | 50/0.25 | 19 | 23 | 12 | 4610 |
| 4.00 | 56/0.30 | 25 | 31 | 8 | 6820 |
| 6.00 | 84/0.30 | 33 | 39 | 6 | 10340 |
| 10.00 | 80/0.40 | 45 | 54 | 1 | 18420 |
| 16.00 | 126/0.40 | 60 | 72 | 1 | 28680 |

KEI CONFLAME - FRLSH PVC INSULATED INDUSTRIAL SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES WITH FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES, WITH FLEXIBLE BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

| CONDUCTOR (AREA SQ.MM) | NO. & SIZE OF WIRE IN MM | Casing (In Conduit / Trunking) | Unenclosed Clipped Directly to surface or on cable tray | STANDARD PACKING FOR 90 MTR. | RATE PER 90MTR. COIL |
|---------------------------|--------------------------------|--------------------------------------|---|------------------------------------|-------------------------|
| 0.50 | 16/0.20 | 5 | 5 | 28 | 1160 |
| 0.75 | 24/0.20 | 9 | 10 | 28 | 1520 |
| 1.00 | 32/0.20 | 14 | 16 | 24 | 2000 |
| 1.50 | 30/0.25 | 17 | 21 | 16 | 2960 |
| 2.50 | 50/0.25 | 23 | 28 | 12 | 4800 |
| 4.00 | 56/0.30 | 31 | 38 | 8 | 7130 |
| 6.00 | 84/0.30 | 40 | 48 | 6 | 10830 |
| 10.00 | 80/0.40 | 54 | 66 | 1 | 19280 |
| 16.00 | 126/0.40 | 74 | 88 | 1 | 30140 |

KEI BANFIRE - SINGLE CORE, UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - ZERO HALOGEN FLAME RETARDANT (ZHFR)/ HALOGEN FREE FLAME RETARDANT (HFFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-17048

| CONDUCTOR (AREA SQ.MM) | NO. & SIZE OF WIRE IN MM | Casing (In Conduit / Trunking) | Unenclosed Clipped Directly to surface or on cable tray | STANDARD PACKING FOR 90 MTR. | RATE PER 90MTR. COIL |
|---------------------------|--------------------------------|--------------------------------------|---|------------------------------------|-------------------------|
| 0.75 | 24/0.20 | 7 | 8 | 28 | 1580 |
| 1.00 | 32/0.20 | 12 | 13 | 24 | 2100 |
| 1.50 | 30/0.25 | 14 | 17 | 16 | 3090 |
| 2.50 | 50/0.25 | 19 | 23 | 12 | 4940 |
| 4.00 | 56/0.30 | 25 | 31 | 8 | 7260 |
| 6.00 | 84/0.30 | 33 | 39 | 6 | 10950 |
| 10.00 | 80/0.40 | 45 | 54 | 1 | 19730 |
| 16.00 | 126/0.40 | 60 | 72 | 1 | 30660 |

Notes:

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- Standard colours in Building wires are RED / BLACK / BLUE / YELLOW / GREEN.
- FR / FRLSH & HFFR (ZHFR) wires are supplied in standard lengths of 90M Coils packed in Master Cartons.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- For other Colours or Lengths please contact our Marketing Department.
- This Price List is subject to change without prior notice.

INDERSONS, S-11 Rajouri Garden, New Delhi 110027 email: sales@indersonsindia.com